


HTM180FH-T82 164W

Open Frame Power

MULTIPLE OUTPUT



UNIVERSAL INPUT

FEATURE

- 90 to 264 VAC universal input
- Built-in EMI filter
- 100% burn-in
- Input surge current protection
- Over voltage protection
- Over current protection
- Temperatures protectio
- Open PCB construction
- PS-ON control
- Power factor correction > 0.9 at full load
- POWER Saving < 0.15W at 230VAC

ENVIRONMENTAL

- Operating temperature: 0°C ~ +50°C
- Operating humidity: 20% ~ 85%
- Storage temperature: - 40°C~ +70°C
- Storage humidity: 10% ~ 95%


Output Voltage/Current Rating Chart

Model Name	Output	V norm.	I min.	I max.	Tolerance	Output Power Max.
HTM180FH-T82	#1	24V	0A	4A	±5%	164W
	#2	12V	0A	4A	±5%	
	#3	5V	0A	3A	±5%	
	#4	+5Vsb	0A	1A	±5%	

Power Saving Sandard Mode High Performance

DIMENSION

- L180x W100x H30mm(Max.)



GENERAL SPECIFICATION

- Efficiency **85% type at full load**
- Hold- up time **8ms at full load, (115V)**
- Inrush current **80A/230 VAC**
- Withstand voltage **3000 VAC, input to output**
- MTBF **50,000 hours**
- Burn-in **100% for all shipped units**
- EMI requirements **Meets conduction limits of**
a) FCC class B
b) CISPR class B
- Safety requirements **Meets**
a) UL 62368
b) EN 62368



威海電子股份有限公司
WEIHAI POWER ELECTRONICS CO.,LTD.

6F. -6, No.700, Jhongjheng Rd., Jhonghe Dist.,
New Taipei City 235, Taiwan (R.O.C.)
TEL: 886-2-82273718 FAX: 886-2-82273719
E-MAIL: sales@wpe.com.tw